



**WIND TURBINE CONSTANT VOLTAGE
CONTROLLER USING MODIFIED SHEPWM
TECHNIQUE**

by

**MUHAMMAD ZAID BIN AIHSAN
1330911109**

A thesis submitted in fulfillment of the requirement for the degree of
Master of Science (Electrical System Engineering)

**School of Electrical System Engineering
UNIVERSITY MALAYSIA PERLIS**

2016

ACKNOWLEDGEMENT

I would like to express the deepest appreciation to Allah S.W.T, the Most Gracious and Most Merciful for ensuring myself to be healthy and let me completed my study. Second, I would like to thanks to my main supervisor Ir. Dr. Rosnazri bin Ali that has spent his precious time to guide me through this entire project. He has delivered idea and useful guidelines whenever I encounter problems. I also would like to thanks to my research advisor Dr. Leong Jenn Hwai and Mr. Norjasmi Abdul Rahman for the give tremendous idea and good path to solve the research problem. With a solid background both of them for this project, the progress even smoother.

I would also like to thank my family for the full support and assists me, especially in moral and financial aids. Thanks for the support and keep encouraging me to keep doing this research until it is completed. My thanks also to my friends, especially here in UniMAP for the idea sharing and brainstorming during the research progress to complete this project.

Thank you.

TABLE OF CONTENT

PAGE

THESIS DECLARATION	i
ACKNOWLEDGEMENTS	ii
TABLE OF CONTENTS	iii
LIST OF TABLES	viii
LIST OF FIGURES	x
LIST OF ABBREVIATION	xvi
LIST OF SYMBOL	xviii
ABSTRAK	xxi
ABSTRACT	xxii
CHAPTER 1 - INTRODUCTION	1
1.1 Research Background	1
1.2 Problem Statement	2
1.3 Objectives	3

1.4	Scope of Work	3
1.5	Thesis Outline	4
CHAPTER 2 – LITERATURE REVIEW		6
2.1	Introduction	6
2.2	Wind Turbine Generator System	7
2.3	AC/DC Three Phase Rectifier System	7
2.4	DC/DC Converter	8
2.4.1	Boost Converter	9
2.4.2	Proportional-Integral (PI) Boost Converter	11
2.5	DC/AC Inverter	13
2.5.1	Single-Phase Inverter Topology	15
2.5.2	Full Bridge Inverter	16
2.6	Pulse Width Modulation (PWM) Scheme	17
2.6.1	Sinusoidal Pulse Width Modulation (SPWM) Scheme	20
2.6.2	Selective Harmonic Elimination Pulse Width Modulation (SHEPWM) Scheme	24
2.7	Total Harmonic Distortion	29

2.8	Low Pass Filter	30
2.9	Transformer	31
2.10	Sealed Lead Acid Rechargeable Battery	32
CHAPTER 3 – METHODOLOGY		33
3.1	Introduction	33
3.2	Boost Converter Circuit Design	34
3.2.1	PI Controller (MATLAB)	37
3.2.2	Ziegler-Nichols Tuning Methods	39
3.2.3	Hardware Operation of PI Boost Converter	41
3.3	Inverter Circuit Design with Modified SHEPWM Switching	42
3.4	Mathematical Analysis for Inverter Switching Angles	45
3.5	Full Bridge Inverter Programming	50
3.6	Calculated Value for SHEPWM Pulses	52
3.7	Control Circuit	53
3.7.1	Gate Driver	54
3.8	LC Low Pass Filter	55

3.9	Battery Storage Configuration	56
3.10	Hardware and Experimental Setup	57
CHAPTER 4 – RESULTS AND DISCUSSIONS		58
4.1	Introduction	58
4.2	Boost Converter	59
4.2.1	Simulation results	59
4.2.2	Hardware Results	68
4.3	Full bridge inverter	72
4.3.1	Simulation results for SHEPWM pulses generation using MATLAB	72
4.3.2	Hardware results	78
4.3.2.1	Conventional Unipolar SPWM Switching Scheme	78
4.3.2.2	Conventional Unipolar SHEPWM Switching Scheme	83
4.3.2.3	Modified Unipolar SHEPWM Switching Scheme	88
4.4	Battery Discharge Rate	106
CHAPTER 5 – CONCLUSION		108

5.1	Conclusion	108
5.2	Research Contribution	110
5.3	Future Work	110
	REFERENCES	111
	APPENDICES	117
	APPENDIX A : PUBLICATION	117
	APPENDIX B : CALCULATED ANGLES	118
	APPENDIX C : PCB FABRICATIONS	126
	APPENDIX D : COMPONENT LIST	128
	APPENDIX E : MATLAB M-FILE PROGRAM	129
	APPENDIX F : C-PROGRAMMING	156

LIST OF TABLES

NO.		PAGE
3.1	Desired boost converter specification	35
3.2	Ziegler-Nichols Continuous Cycling Formulas	39
3.3	Calculation for desired PI controller design	40
3.4	Summarization of (K_p) and (K_i) gain tuning	40
3.5	Resistor selection for voltage divider	41
3.6	Value of step size according to b-bit vale	42
3.7	Basic structure of inverter switching strategy	51
3.8	Firing angle for modulation index = 1.0	52
4.1	Parameters for boost converter and inverter	59
4.2	The effects of changing the control parameters of PI control	66
4.3	Result of PI boost converter with fixed $R = 25\Omega$	71
4.4	THD performance comparison	94
4.5	Efficiency between three switching strategies	94
4.6	Effect of modulation index to THD performance	95
4.7	Comparison of resistive and inductive load	101

©This item is protected by original copyright

LIST OF FIGURES

NO.		PAGE
2.1	Full design of wind energy conversion	6
2.2	Basic three phase rectifier circuit	8
2.3	Basic boost converter circuit	10
2.4	(a) Turned ON state. (b) Turned OFF state	11
2.5	Boost converter with voltage divider sensor	13
2.6	Half bridge inverter circuit	16
2.7	Full bridge inverter circuit	17
2.8	The natural sampling PWM	18
2.9	Intersection point between sinusoidal and triangle	18
2.10	Unipolar SPWM switching scheme	21
2.11	The conventional switching of SPWM	22
2.12	The new proposed switching strategy	24
2.13	The definition of angles to be calculated using Fourier series	26
2.14	LC filter	31
2.15	Step up toroidal transformer	32

3.1	Project flowchart	33
3.2	Simulation circuit of DC/DC boost converter	34
3.3	Hardware circuit of DC/DC boost converter	36
3.4	Overshoot inductor current	37
3.5	Block diagram of PI controller	38
3.6	Output response for Ziegler-Nichols Continuous Cycling Method	39
3.7	Graphical of tuning parameters	40
3.8	(a) SHEPWM Modified Unipolar Inverter, (b) The subsystem design of SHEPWM pulses and (c) Internal design for each SHEPWM block	44
3.9	Hardware design of DC/AC inverter	44
3.10	The beginning part of MATLAB command	47
3.11	Second part of MATLAB code	49
3.12	Graphical illustration of modified switching strategy as in Table 3.1	52
3.13	SK40C schematic	53
3.14	Gate driver design	54
3.15	LC filter implementation	56
3.16	Battery configuration	56

3.17	The whole circuit design	57
4.1	Closed loop boost converter circuit	60
4.2	The internal block for PI controller	60
4.3	(a) Intersection duty with triangle (b) Generated pulses	61
4.4	(a) Input voltage, (b) Output voltage and (c) Error of voltage	61
4.5	(a) Inductor current and (b) Output current	62
4.6	(a) Intersection duty with triangle (b) Generated pulses	62
4.7	(a) Input voltage, (b) Output voltage and (c) Error of voltage	63
4.8	(a) Inductor current and (b) Output current	63
4.9	(a) Intersection duty with triangle (b) Generated pulses	64
4.10	(a) Input voltage, (b) Output voltage and (c) Error of voltage	64
4.11	(a) Inductor current and (b) Output current	65
4.12	(a) Varies input voltage (b) Output voltage	67
4.13	Changing of duty cycle	68
4.14	Boost converter results ($V_{in} = 28.4 \text{ V}$, $V_{out} = 50.6 \text{ V}$, $D = 0.44$)	69
4.15	Boost converter results ($V_{in} = 24.2 \text{ V}$, $V_{out} = 50.5 \text{ V}$, $D = 0.52$)	69
4.16	Boost converter results ($V_{in} = 22.3 \text{ V}$, $V_{out} = 50.2 \text{ V}$, $D = 0.56$)	69

4.17	Boost converter results ($V_{in} = 18.2 \text{ V}$, $V_{out} = 50.6 \text{ V}$, $D = 0.64$)	69
4.18	The zoom in version of voltage spike	71
4.19	The RC snubber-circuit configuration	72
4.20	Generated SHEPWM pulses	73
4.21	Comparison of new switching strategy and the conventional switching strategy	74
4.22	(a) FFT spectrum of new switching strategy. (b) FFT spectrum of the conventional switching strategy. Comparison of THD spectrum for both switching strategy	75
4.23	The harmonics order form 1 st to 9 th order	76
4.24	The harmonics order form 91 st to 99 th order	77
4.25	3 rd and 5 th harmonic content	77
4.26	7 th and 9 th harmonic content	78
4.27	97 th and 99 th harmonic contents	78
4.28	Generated pulses for S1, S2, S3 and S4.	79
4.29	Design of dead time for S1 and S3	79
4.30	Output voltage of the unipolar SPWM inverter	80
4.31.	The level of THD before filtering process	81
4.32	Input voltage and current for the SPWM inverter	81

4.33	Output voltage and current for the SPWM inverter	82
4.34	Value of THD voltage	82
4.35	Value of THD current	83
4.36.	Generated SHEPWM pulses for S1, S2, S3 and S4	84
4.37	Output voltage of the unipolar SHEPWM inverter	85
4.38	The level of THD before filtering process	85
4.39	Input voltage and current for the SHEPWM inverter	86
4.40	Output voltage and current for the SHEPWM inverter	86
4.41	Value of THD voltage	87
4.42	Value of THD current	87
4.43	The generated pulses for all MOSFETs	89
4.44	(a) Gate pairing between S1S2 (b) Gate pairing between S3S4	89
4.45	The output of the modified Unipolar SHEPWM	90
4.46	The level of THD before filtering process from 3 rd – 25 th	91
4.47	The level of THD before filtering process from 27 th – 49 th	91
4.48	Input voltage and current for the modified switching scheme	92

4.49	Output voltage and current for the modified switching scheme	92
4.50	Value of THD voltage	93
4.51	Value of THD current	93
4.52	THD versus modulation index	95
4.53	Efficiency versus modulation index	96
4.54	The comparison of voltage at primary and secondary windings	97
4.55	Output voltage and current at the secondary side	97
4.56	THD voltage at secondary side	98
4.57	THD current secondary side	98
4.58	The comparison of voltage at primary and secondary side	99
4.59	Output voltage and current at the secondary side	99
4.60	THD voltage after transformer	100
4.61	THD current after transformer	100
4.62	Comparison of LC filter design based on capacitor configuration	103

LIST OF ABBREVIATION

DC	Direct Current
AC	Alternating Current
PV	Photovoltaic
HAWT	Horizontal Axis Wind Turbine
VAWT	Vertical Axis Wind Turbine
MAGLEV	Magnetic Levitation
PI	Proportional Integral
PWM	Pulse Width Modulation
SPWM	Sinusoidal Pulse Width Modulation
SHEPWM	Selective Harmonic Elimination Pulse Width Modulation
PCB	Printed Circuit Board
LC	Low pass filter
WTGS	Wind Turbine Generator System Effect
SMPS	Switched Mode Power Supply

MOSFET	Metal Oxide Semiconductor Field Effect Transistor
IGBT	Insulated Gate Bipolar Transistor
CCM	Continuous conduction mode
DCM	Discontinuous Conduction Mode
VSI	Voltage Source Inverter
CSI	Current Source Inverter
THD	Total Harmonic Distortion
Hz	Hertz
kHz	kilo Hertz
IEEE	Institute of Electrical and Electronic Engineer

©This item is protected by original copyright

LIST OF SYMBOL

V_{dc}	Direct Current Voltage
V_{ac}	Alternating Current Voltage
V	Voltage
I	Current
P	Power
V	Volts
A	Ampere
W	Watt
V_A	Voltage Phase A
V_B	Voltage Phase B
V_C	Voltage Phase C
D	Diode
R	Resistor
C	Capacitor
L	Inductor
V_s	Supply voltage
v_L	Voltage across inductor
i_L	Current across inductor

i_C	Current across capacitor
v_o	Output voltage
S_1	Switch 1
S_2	Switch 2
S_3	Switch 3
S_4	Switch 4
D	Duty cycle
T_{on}	Time on
T_{off}	Time off
T_s	Sampling time
V_{SENSE1}	Sensor voltage 1
V_{SENSE2}	Sensor voltage 2
m_f	Frequency modulation
m_a	Amplitude modulation
$f_{carrier}$	Carrier frequency
$f_{reference}$	Reference frequency
f_{tri}	Triangular frequency
f_{sin}	Sinusoidal frequency
$V_{m,reference}$	Reference voltage

$V_{m,\text{carrier}}$	Carrier voltage
A_r	Reference amplitude
A_c	Carrier amplitude
π	Pi
ω	Omega
t	Time
θ	Theta
α	Alpha
η	Efficiency
Ω	Ohm
f_{sw}	Switching frequency

©This item is protected by original copyright

PENGAWAL TURBIN ANGIN DENGAN VOLTAN MALAR MENGGUNAKAN TEKNIK PENGUBAHSUAIAN SHEPWM

ABSTRAK

Cabaran utama dalam merekabentuk pengawal ini adalah kelajuan turbin angin yang tidak sekata dan kandungan harmonik dalam keluaran voltan. Kelajuan turbin yang tidak sekata ini akan menyebabkan ketidakselarasan voltan yang bakal dibekalkan kepada penyongsang dan seterusnya memberi kesan kepada dengan munculnya harmonik pada keluaran voltan. Oleh itu, kajian ini adalah khusus untuk mereka bentuk pengawal terdiri daripada DC/DC penukar rangsangan dan penyongsang DC/AC bersepadu dengan sistem turbin angin. Pengawal ini memainkan dua peranan penting. Pertama, pengawal perlu mengawal keselerasan voltan keluaran DC/DC penukar rangsangan tanpa mengira ketidakselarasan voltan input yang dibekalkan menggunakan pengawal PI. Kedua, pengawal perlu menjana sudut yang tidak menjana harmonik untuk fasa tunggal DC/AC penyongsang menggunakan strategi Pulse Selective Harmonic Penghapusan lebar modulasi (SHEPWM). Sistem keseluruhan telah berjaya dibentuk dengan menggunakan perisian MATLAB Simulink dan dilaksanakan menggunakan perkakasan sebenar. Keputusan daripada kedua-dua simulasi dan perkakasan dikumpul, dianalisis dan dibandingkan. Perkakasan yang diuji dengan beban rintangan dan beban induktif untuk mengkaji prestasi pengawal apabila berurusan dengan pelbagai jenis beban. Daripada keputusan yang diperolehi daripada simulasi dan perkakasan, dapat disimpulkan bahawa litar pengawal direka berfungsi dengan baik walaupun voltan input yang dibekalkan kepada rangsangan penukar berbeza dan voltan keluaran penyongsang adalah sangat rendah dalam jumlah herotan harmonik (THD) hampir 3.6 % untuk voltan THD dan 2.1% untuk THD arus.

WIND TURBINE CONSTANT VOLTAGE CONTROLLER USING MODIFIED SHEPWM TECHNIQUE

ABSTRACT

The major challenges in designing the controller for wind turbine are fluctuations of the wind speed and the harmonic contents of the output voltage. The fluctuations of the wind turbine speed results in inconsistency of voltage supplied to the inverter which will affect the harmonic of the output voltage. Therefore, this research is dedicated to design a controller consists of a DC/DC boost converter and a DC/AC inverter integrated with the wind turbine system. The controller plays two important roles. Firstly, the controller has to control the consistency of the output voltage of the DC/DC boost converter irrespective of the inconsistency of the input voltage supplied using PI controller. Second, the controller has to generate the firing angles that giving out lesser harmonic to the single phase DC/AC inverter using the Selective Harmonic Elimination Pulse Width Modulation (SHEPWM) switching strategy. The overall system has been designed successfully using MATLAB Simulink software and implemented using real hardware. The results from both simulation and hardware are collected, analysed and compared. For boost converter, the output voltage is in constant 50V even though the input voltage supplied to the boost converter is varies and it is suitable to charge the battery system. For inverter, the hardware is tested with a resistive load and an inductive load to study the performance of the controller when dealing with different types of load. From the results obtained from simulation and hardware, it can be concluded that the designed controller circuit is working well even though the input voltage supplied to the boost converter varies and the output voltage of inverter is very low in total harmonic distortion (THD) nearly 3.6% for THD voltage and 2.1% for THD current.

CHAPTER 1

INTRODUCTION

1.1 Research Background

According to the law of energy conservation, energy cannot be created or demolished but can be converted from one form to another. There are various naturally available energies such as solar energy, wind energy, thermal energy, and tidal wave energy. These energies can be harnessed and converted into usable form using specific tools and equipment.

In electrical energy, the electricity can flow as either direct current (DC) or alternating current (AC). In DC, the electricity flows in a one direction and normally used in lower power or battery powered devices such as mobile phone, remote control and most of kid's toys. Whilst for AC, it has two magnitudes of voltage positive and negative oscillating between 0 intersections at X-axis with a specific frequency. AC is usually used for powering the standard household appliances.

In Malaysia, harvesting the solar energy via photovoltaic (PV) is preferable as this country is located close to the Equator, blessed with adequate sunlight radiation throughout the year. Wind energy however is somehow neglected as Malaysia is located in between Thailand, Indonesia and Philippines, thus blocking the potential of harvesting energy from high wind speed. The annual average wind speed in Malaysia is not more than 2m/s which is not enough to move the blades of the normal scale wind

turbine (Christopher, 2010). Due to this reason, generating the electricity from wind energy is hard to achieve.

These weaknesses are studied and there is an option to overcome this problem. For the wind turbine system, there are two systems which are horizontal axis wind turbine (HAWT) and vertical axis wind turbine (VAWT). The HAWT system is used for high wind speed applications whilst VAWT is purposely designed for low wind speed applications. With some modifications by incorporating the magnetic levitation (MAGLEV) concept to the VAWT system, the blade is levitated by the nature of the magnetic force providing easier wind turbine blade rotation. The capability of VWAT is proven that the turbine blade can be rotated at wind speed as low as 1.5m/s (Baharudin & Mansur, 2013)

By using VWAT, the consumers in Malaysia are able to utilize this naturally available energy rather than being wasted. The small scale VAWT with the rating of 300W 24V can be implemented to the residential in Malaysia by mounting the VAWT on the roof top. This converter is designed as standalone electricity generation in the house without dealing with any grid connected system.

For remote locations, PV and wind turbine system can be installed to generate electricity as the electrical grid cannot be reached at some locations, for example remote communities. By incorporating both solar and wind energy generation, it will improve the living quality for those living in that areas.

1.2 Problem Statement

When designing a power converter for a wind turbine, the fluctuations of the wind speed is the major challenge as it can affect the consistency of the output voltage