



**MULTI-WAVELENGTH BRILLOUIN FIBER
LASER BY UTILIZING FIBER BRAGG GRATING**

by

**AMIRA ZAKIAH BINTI MALEK
(1330111111)**

A thesis submitted in fulfillment of the requirements for the degree of
Master of Science in Microelectronic Engineering

**School of Microelectronic Engineering
UNIVERSITI MALAYSIA PERLIS**

2017

ACKNOWLEDGEMENT

Alhamdulillah, first and foremost, I would like to take this opportunity to express my sincere appreciation to everyone who were involved in my Master Project, either directly or indirectly, and have aided me through the difficulties and crucial times. Though I had a tough time, with the help of caring, understanding and helpful people, I have managed to finish this report. This Master Project has truly been an educational and significant experience for me.

A special thank goes to my beloved husband, Mr. Azmeer Zairee bin Omar and my father Mr. Malek bin Deraman for their constant support during my research project. The encouragement and motivation they have shown in me is my greatest source of inspiration. I also would like to convey my special gratitude towards my respectful supervisor, Dr. Nor Azura Malini binti Ahmad Hambali. The supervision that she gave truly helps the progression and smoothness of the Master Project. I am forever grateful for being welcomed into your group. Your time, patience, and interest in my work have never gone unnoticed. The cooperation is indeed much appreciated. Not forget, great appreciation goes to my co-supervisor, Dr. Mohamad Halim bin Abdul Wahid that helped me from time to time during the project. I would like also to acknowledge with much appreciation for staff of School of Microelectronics Engineering, Mr. Mohd Azarulsani Bin Md. Azidin who gave his critical comments and constructive suggestions for my project and final report. My many thanks also go to all my fellow friends for their patience, cooperation and assistance provided in completing my Master Project. The whole project really brought us together to appreciate the true value of friendship and respect each other. Also, not forgetting my family members who always been there through my ups and downs during the completion of this project. Their ideas,

suggestions, advice and guidance have really helped me to improve and realize the objective of this Master Project.

Thank you.

© This item is protected by original copyright

TABLE OF CONTENTS

	PAGE
THESIS DECLARATION	i
ACKNOWLEDGEMENT	ii
TABLE OF CONTENTS	iv
LIST OF FIGURES	viii
LIST OF TABLES	xiv
LIST OF ABBREVIATIONS	xv
LIST OF SYMBOLS	xvii
ABSTRAK	xix
ABSTRACT	xx
CHAPTER 1 INTRODUCTION	
1.1 Overview	1
1.2 Problem statement	4
1.3 Aim and motivation	6
1.4 Objectives	6
1.5 Scopes of work	7
1.6 Thesis organization	8
CHAPTER 2 LITERATURE REVIEW	
2.1 Light interaction in the optical fiber	11
2.2 Nonlinear effects in optical fibers	12
2.3 Stimulated Brillouin scattering	13
2.4 Single mode fiber	14
2.5 Laser	15

2.6	Principle of laser	16
2.7	Fiber laser	18
2.8	Brillouin threshold	19
2.9	Theory of Brillouin gain	21
2.10	Optical signal to noise ratio (OSNR)	26
2.11	Erbium doped fiber amplifiers (EDFA)	27
2.12	980 nm pump laser	28
2.13	1480 nm pump laser	30
2.14	Fiber Bragg grating	31
2.15	Laser cavity	33
2.16	Single-wavelength fiber laser	34
2.17	Multi-wavelength fiber laser	36
2.18	Reviews on previous work	38
CHAPTER 3 METHODOLOGY		
3.1	General research development	45
3.2	Equipments and components	46
3.3	The general flow chart of MWBFL utilizing FBG	48
3.4	The characterization of single-wavelength linear cavity BFL system	50
3.5	The optimization of number BS signals and average OSNR value based on the variation output coupling ratios and fiber lengths	53
3.6	Fiber lengths optimization at 90% optimum output coupling ratio based on different amplified BP powers	56
3.7	The optimization of amplified BP powers by utilizing 90% optimum output coupling ratio at 10 km of SMF	58
3.8	Conclusion	61

CHAPTER 4 RESULTS AND DISCUSSION

4.1	Experiment setup of single wavelength linear cavity BFL system	63
4.2	The characterization of transmission and reflection of FBG	65
4.3	Optical spectra of linear cavity BFL by using FBG and without FBG	67
4.4	BS signal versus amplified BP power by using FBG and without FBG	68
4.5	The OSNR value versus amplified BP power by using FBG and without FBG	69
4.6	BS signal power versus wavelength by using FBG and without FBG	71
4.7	The threshold power linear cavity BFL by using FBG and without FBG	72
4.8	Conclusion	74

CHAPTER 5 RING CAVITY MWBFL UTILIZING FBG

5.1	Experimental setup of ring cavity MWBFL utilizing FBG	76
5.2	Brillouin threshold power for first BS signal	78
5.3	The optimization of generated BS signals and average OSNR value	83
5.4	The optimization of SMF length for ring cavity MWBFL utilizing FBG at 90% optimum output coupling ratio based on different amplified BP powers	100
5.5	The optimization of amplified BP powers by utilizing 90% optimum output coupling ratio at 10 km of SMF	118
5.6	Conclusion	127

CHAPTER 6 CONCLUSION AND FUTURE WORK

6.1	Performance Comparison	129
6.2	Conclusion	130
6.3	Recommendation for future work	134

REFERENCES

APPENDIX A

LIST OF PUBLICATIONS

LIST OF FIGURES

NO.		PAGE
1.1	Flow chart scopes of work	8
2.1	Schematic diagram of the SBS process in the optical fiber	14
2.2	Propagation rays of single mode fiber	15
2.3	Absorption, spontaneous emission and stimulated emission	16
2.4	The output spectra of BS signal at different injected BP power	20
2.5	The BS signal power as a function of the Brillouin pump power	21
2.6	Measurement of the OSNR value	27
2.7	Basic configuration of EDFA	28
2.8	Pumping scheme of three-level energy	29
2.9	Pumping scheme of two-level energy	30
2.10	The cross section of Bragg grating	31
2.11	The basic principle of FBG with incident, transmitted and reflected spectrum	32
2.12	Optical structure of linear cavity	34
2.13	Optical structure of ring cavity	34
2.14	Optical spectra of a single wavelength generation	35
2.15	Multi-wavelength generation	36
2.16	Experimental setup for generation of 10 GHz and 20 GHz combs	38
2.17	Structure for multi-wavelength BFL with double Brillouin frequency shift	40
3.1	Flow chart of general research development	46
3.2	General flow chart of MWBFL utilizing FBG	49
3.3	The methodology flow of the linear cavity BFL system	51
3.4	The methodology flow of optimization number BS signals and average	55

	OSNR value produced based on the variation coupling ratios and fiber lengths	
3.5	The methodology flow of fiber length optimization at 90% optimum output coupling ratio based on different amplified BP powers	57
3.6	The optimization of amplified BP powers by utilizing 90% optimum output coupling ratio at 10 km of SMF	59
4.1	Configuration of single-wavelength BFL operated in the C-band wavelength without utilizing FBG	64
4.2	Configuration of single-wavelength BFL operated in the C-band wavelength with utilizing FBG	64
4.3	Transmission and reflection spectra of the FBG	66
4.4	Output spectrum of the BS signal by using FBG and without FBG at amplified BP power of 25 dBm	67
4.5	BS signal versus amplified BP power within 18 dB to 27.5 dBm	68
4.6	OSNR versus amplified BP power within 18 dB to 27.5 dBm	70
4.7	BS signal versus C-band wavelength region at 15.5 dBm of amplified BP power	71
4.8	Output optical spectrum of the BFL without FBG operating at different amplified BP powers	73
4.9	Output optical spectrum of the BFL with FBG operating at different amplified BP powers	74
5.1	Multi-wavelength BFL configuration utilizing FBG	77
5.2	Brillouin threshold power at different output coupling ratios by utilizing 10 km of SMF	79
5.3	Output spectra of the ring cavity MWBFL utilizing FBG at different threshold condition: (a) below, (b) around, (c) above and (d)	80

	multi-wavelength generation	
5.4	Brillouin threshold power at different coupling ratios and fiber lengths	82
5.5	Output spectra at different amplified BP power by using 80% output coupling ratio at 11 km	83
5.6	The number BS signals versus amplified BP power from 8 dBm to 18 dBm by utilizing 8 km of SMF at the BP wavelength of 1550 nm	85
5.7	Optical spectra at 90% output coupling ratio with 18 dBm of amplified BP power by utilizing 8 km of SMF, (a) generated optical spectrum and (b) magnified view.	86
5.8	The number BS signals versus amplified BP power from 8 dBm by utilizing 9 km of SMF at the BP wavelength of 1550 nm	87
5.9	Optical spectra at 90% output coupling ratio with 18 dBm of amplified BP power by utilizing 9 km of SMF, (a) generated optical spectrum and (b) magnified view.	87
5.10	The number BS signals versus amplified BP power from 8 dBm to 18 dBm by utilizing 10 km of SMF at the BP wavelength of 1550 nm	88
5.11	Optical spectra at 90% output coupling ratio with 18 dBm of amplified BP power by utilizing 10 km of SMF, (a) generated optical spectrum and (b) magnified view.	89
5.12	The number BS signals versus amplified BP power from 8 dBm to 18 dBm by utilizing 11 km of SMF at the BP wavelength of 1550 nm	90
5.13	Optical spectra at 90% output coupling ratio with 18 dBm of amplified BP power by utilizing 11 km of SMF, (a) generated optical spectrum and (b) magnified view.	90
5.14	The number BS signals versus amplified BP power from 8 dBm to 18 dBm	91

- by utilizing 12 km of SMF at the BP wavelength of 1550 nm
- 5.15 Optical spectra at 90% output coupling ratio with 18 dBm of amplified BP 92
power by utilizing 12 km of SMF, (a) generated optical spectrum and (b)
magnified view.
- 5.16 The average OSNR value versus amplified BP power from 8 dBm to 18 dBm 93
by utilizing 8 km of SMF at the BP wavelength of 1550 nm
- 5.17 The average OSNR value versus amplified BP power from 8 dBm to 18 dBm 95
by utilizing 9 km of SMF at the BP wavelength of 1550 nm
- 5.18 The average OSNR value versus amplified BP power from 8 dBm to 18 dBm 96
by utilizing 10 km of SMF at the BP wavelength of 1550 nm
- 5.19 The average OSNR value versus amplified BP power from 8 dBm to 18 dBm 98
by utilizing 11 km of SMF at the BP wavelength of 1550 nm
- 5.20 The average OSNR value versus BP power from 9 dBm to 18 dBm by 99
utilizing 12 km of SMF at the BP wavelength of 1550 nm
- 5.21 The number BS signals and anti-Stokes signals versus different SMF lengths 101
by injected 8 dBm amplified BP power at BP wavelength of 1550 nm
- 5.22 The number BS signals and anti-Stokes signals versus different SMF lengths 102
by injected 9 dBm amplified BP power at BP wavelength of 1550 nm
- 5.23 The number BS signals and anti-Stokes signals versus different SMF lengths 103
by injected 10 dBm amplified BP power at BP wavelength of 1550 nm
- 5.24 The number BS signals and anti-Stokes signals versus different SMF lengths 104
by injected 11 dBm amplified BP power at BP wavelength of 1550 nm
- 5.25 The number BS signals and anti-Stokes signals versus different SMF lengths 104
by injected 12 dBm amplified BP power at BP wavelength of 1550 nm
- 5.26 The number BS signals and anti-Stokes signals versus different SMF lengths 106

	by injected 13 dBm amplified BP power at BP wavelength of 1550 nm	
5.27	The number BS signals and anti-Stokes signals versus different SMF lengths 107 by injected 14 dBm amplified BP power at BP wavelength of 1550 nm	
5.28	The number BS signals and anti-Stokes signals versus different SMF lengths 107 by injected 15 dBm amplified BP power at BP wavelength of 1550 nm	
5.29	The number BS signals and anti-Stokes signals versus different SMF lengths 108 by injected 16 dBm amplified BP power at BP wavelength of 1550 nm	
5.30	The number BS signals and anti-Stokes signals versus different SMF lengths 108 by injected 17 dBm amplified BP power at BP wavelength of 1550 nm	
5.31	The number BS signals and anti-Stokes signals versus different SMF lengths 109 by injected 18 dBm amplified BP power at BP wavelength of 1550 nm	
5.32	The average OSNR value versus SMF lengths with different injected BP powers	110
5.33	The number BS signals and average OSNR value versus different SMF lengths within 8 km to 12 km at amplified BP power of 12 dBm	112
5.34	The number BS signals and average OSNR value versus different SMF lengths within 8 km to 12 km at amplified BP power of 13 dBm	113
5.35	The number BS signals and average OSNR value versus different SMF lengths within 8 km to 12 km at amplified BP power of 14 dBm	114
5.36	The number BS signals and average OSNR value versus different SMF lengths within 8 km to 12 km at amplified BP power of 15 dBm	115
5.37	The number BS signals and average OSNR value versus different SMF lengths within 8 km to 12 km at amplified BP power of 16 dBm	116
5.38	The number BS signals and average OSNR value versus different SMF lengths within 8 km to 12 km at amplified BP power of 17 dBm	117

5.39	The number BS signals and average OSNR value versus different SMF lengths within 8 km to 12 km at amplified BP power of 18 dBm	118
5.40	The BS signal power versus amplified BP power at 90% optimum output coupling ratio by utilizing 10 km of SMF	119
5.41	The output optical spectra of MWBFL utilizing FBG at different amplified BP power of 8 dBm to 11 dBm	121
5.42	The output optical spectra of MWBFL utilizing FBG at minimum of 8 dBm to the maximum of 18 dBm amplified BP power	121
5.43	The number BS signals and anti-Stokes signals versus amplified BP power from 11 dBm to 18 dBm at BP wavelength of 1550 nm	122
5.44	The correlation between number BS signals and average OSNR value with different amplified BP at 1550 nm of BP wavelength	124
5.45	The number BS signals versus BP wavelengths at 90% optimum output coupling ratio with different amplified BP powers	125
5.46	The generated output spectra at the tuning range of 1546 nm to 1554 nm of BP wavelengths by injected 18 dBm of amplified BP power.	126

LIST OF TABLES

NO.		PAGE
2.1	Summaries of the previous papers for MWBFL system	42
3.1	Equipments and components used in the experimental work.	47
6.1	Performance comparison of MWBFL system	129

© This item is protected by original copyright

LIST OF ABBREVIATIONS

SBS	Stimulated Brillouin scattering
BS	Brillouin Stokes
BP	Brillouin pump
SMF	Single mode fiber
MWBFL	Multi-wavelength Brillouin fiber laser
BFL	Brillouin fiber laser
EDFA	Erbium doped fiber amplifier
DWDM	Dense wavelength division multiplexing
MWBEFL	Multi-wavelength Brillouin-Erbium fiber laser
MWBRFL	Multi-wavelength Brillouin Raman fiber laser
EDF	Erbium doped fiber
SRS	Stimulated Raman scattering
DCF	Dispersion compensating fiber
FBG	Fiber Bragg grating
OSNR	Optical signal to noise ratio
BEFL	Brillouin Erbium fiber laser
BRFL	Brillouin Raman fiber laser
SPM	Self-phase modulation
XPM	Cross phase modulation
FWM	Four wave mixing
MWEDFL	Multi-wavelength Erbium doped fiber laser
WDM	Wavelength division multiplexer
OSA	Optical spectrum analyser

PCF	Photonic crystal fiber
HNLF	Highly nonlinear fiber
TLS	Tunable laser source
SSMF	Standard single mode fiber

© This item is protected by original copyright

LIST OF SYMBOLS

nm	Nanometer
mW	Miliwatt
dBm	dB relative to a miliwatt
dB	Decibel
km	Kilometer
ms	Millisecond
%	Percentage
GHz	Gigahertz
v_A	The acoustic velocity in the gain medium
λ_p	The pump wavelength
n	The fiber refractive index
E_1	Energy potential of the ground state
E_2	Energy potential of the excited state
h	Planck's constant
ν	Frequency of the photon
$\alpha_p \approx \alpha_s \equiv \alpha$	Fiber losses are nearly the same for the stoke waves
$\omega_p \approx \omega_s$	Small value of the Brillouin shift
g_B	Brillouin gain coefficient
α	Fiber loss coefficient
I_s	BS signal intensity
I_p	BP signal intensity
G_B	The unsaturated Brillouin gain
L	Fiber length

A_{eff}	Effective core area of the fiber
$I_p(0)$	Pump signal intensity at the initial condition
b_0	The portion of the input pump power that is converted to the BS power
g_0	Small signal gain that is associated with the SBS process
Er^{3+}	Erbium ion
n_1	High refractive index
n_2	Low refractive index
λ_B	Back-reflected light
R	Final reflectance
l	Length of the grating
k	Characteristic of FBG parameter
λ	Operating wavelength
Δn	Amplitude of the index variation
kHz	Kilohertz

© This item is protected by original copyright

Pelbagai Gelombang Gantian Brillouin Laser Dengan Menggunakan Gantian Bragg

ABSTRAK

Sebuah rongga cincin pelbagai panjang gelombang gantian Brillouin laser dengan menggunakan gantian Bragg dimanipulasikan untuk meningkatkan penghantaran atau kadar data dalam komunikasi gantian optik terutamanya di dalam sistem pemultipleksan pembahagian panjang gelombang tumpat. Gabungan kesan berselerak Brillouin dan pembalik cahaya di dalam gantian Bragg telah meningkatkan penjanaan pelbagai gelombang untuk menghantar maklumat yang banyak pada waktu yang sama. Tatarajah rongga cincin telah dieksperimen dengan menggunakan pelbagai panjang gantian mod tunggal di mana ianya bertindak sebagai medium bagi mendapatkan keuntungan Brillouin dan seterusnya merangsang kesan Brillouin berselerak. Kuasa pam Brillouin dilaraskan dari 8 dBm kepada 18 dBm dengan menaikkan kuasa sebanyak 1 dBm secara berperingkat ke dalam sistem laser. Lima panjang gantian mod tunggal yang berbeza sepanjang 8 km, 9 km, 10 km, 11 km and 12 km beserta sembilan nisbah gandingan pengeluaran dari 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80% dan 90% telah dioptimumkan untuk menjana lebih banyak keluaran isyarat. Secara keseluruhannya, keputusan menunjukkan penyiasatan mengenai ambang kuasa Brillouin untuk isyarat Brillouin Stokes yang pertama bergantung kepada panjang gantian mod tunggal and nisbah gandingan pengeluaran. Ambang kuasa Brillouin terendah sebanyak 8 dBm direkodkan apabila 10%, 20%, 30% and 40% daripada nisbah gandingan pengeluaran serta 10 km panjang gantian mod tunggal digunakan ke dalam rongga cincin manakala ambang kuasa Brillouin yang paling tinggi sebanyak 12 dBm dicatatkan dengan menggunakan 8 km panjang gantian mod tunggal pada 60%, 70%, 80% dan 90% nisbah gandingan pengeluaran. Selain daripada itu, sehingga maksimum 38 isyarat Brillouin Stokes bersama-sama dengan 16.00 dB purata nilai optik isyarat kepada nisbah hingar direkodkan pada 1550 nm untuk pelbagai panjang gelombang Brillouin pam apabila pam Brillouin dilaraskan sehingga 18 dBm telah dimasukkan ke dalam rongga cincin. Sebanyak 90% optimum nisbah keluaran gandingan dan 10 km gantian mode tunggal telah digunakan dalam menghasilkan generasi pelbagai panjang gelombang. Kekurangan pemilihan panjang gelombang adalah berdasarkan oleh ciri-ciri gantian Bragg itu sendiri. Generasi pelbagai panjang gelombang hanya berlaku dalam lingkungan 1544 nm hingga ke 1556 nm untuk pam Brillouin panjang gelombang mengikut 3 dB jalur lebar 5 nm daripada gantian Bragg. Pendek kata, prestasi projek yang lebih baik terhasil daripada pelbagai gelombang gantian Brillouin laser dengan menggunakan gantian Bragg di mana generasi pelbagai panjang gelombang yang paling berkesan dihasilkan dengan menggunakan 10 km medium keuntungan Brillouin.

Multi-Wavelength Brillouin Fiber Laser By Utilizing Fiber Bragg Grating

ABSTRACT

A ring cavity multi-wavelength Brillouin fiber laser by utilizing fiber Bragg grating is evolved to increase the transmission or data rate in the optical fiber communication especially in dense wavelength division multiplexing system. The combination of stimulated Brillouin scattering effect and fiber Bragg grating's reflectivity enhances the multi-wavelength generation in order to transmit a lot of information at the same time. A ring cavity configuration has been experimental demonstrated with different single mode fiber lengths in which act as a Brillouin gain medium in stimulated Brillouin scattering effect. The amplified Brillouin pump power of 8 dBm to 18 dBm with a step increment of 1 dBm was applied in the laser system. Five different single mode fiber lengths of 8 km, 9 km, 10 km, 11 km and 12 km with nine output coupling ratios of 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80% and 90% were optimized to generate more output signals. Overall, the results showed that the investigation of Brillouin threshold power for first Brillouin Stokes signals was critically depends on the selective single mode fiber lengths and output coupling ratios. The lowest Brillouin threshold power of 8 dBm was achieved when 10%, 20%, 30% and 40% of the output coupling ratio at 10 km of single mode fiber was applied into the ring cavity while the highest Brillouin threshold power of 12 dBm was recorded by using 8 km of single mode fiber with 60%, 70%, 80% and 90% of output coupling ratios. Besides that, up to maximum 38 generated Brillouin Stokes signals with 16.00 dB of average optical signal to noise ratio value were recorded at 1550 nm of Brillouin pump wavelength when high amplified Brillouin pump power of 18 dBm was injected into the ring cavity. An optimum output coupling ratio of 90% and 10 km of single mode fiber were utilized in producing the multi-wavelength generation. The wavelength selectivity based on the Fiber Bragg Grating's properties constrains the tuning range ability of this laser system. The multi-wavelength generation only occurred within 1544 nm to 1556 nm of Brillouin Pump wavelength according to the 3 dB bandwidth of 5 nm of the fiber Bragg grating. In short, the better performance of multi-wavelength Brillouin Fiber Laser by utilizing fiber Bragg grating was successfully demonstrated whereby the most multi-wavelength generation produced at 10 km of the effective Brillouin gain medium.

CHAPTER 1

INTRODUCTION

In this chapter explains an overview of the fiber optic communication system and its application in order to understand the whole concept of this research work. The topics were divided into different view such as overview, problem statement, aim and motivation, objectives and scopes of work. The demand of optical fiber for more communication application also deeply explained at the end of this chapter.

1.1 Overview

Generally, the invention based on the fiber optic communication system is mainly known as a technology of transmitting the desired amount of data or information from one location to another by propagating light pulses through an optical fiber (Dike & Ogbe, 2013). Prior to the innovation of the fiber optics, worldwide communication utilizes copper wire as a main medium for communication (Personick, Rhodes, Hanson & Chan, 1980). However, this electrical transmission is not relevant today especially for a long haul communication due to the limitation of huge size and the difficulties of installation (Agrawal, 2002).

Over many decades, fiber optic has tremendously transformed the telecommunication industry in many aspects and offers the reliable data innovation for internet users either in terms of global coverage or data rates (Kinlin, 2006). This growth is due to the development of a wide tuning range of the fiber laser system which offers almost unlimited bandwidth at higher speed (Ahmad et al., 2012). As the interest

for data transfer expands, this situation increased the great opportunity to more research and investigation on new applications and technologies.

Since the first investigation of stimulated Brillouin scattering (SBS) effect has been studied in 1964 by (Chiao, Townes & Stoicheff, 1964), the deployment of light for fiber optic communication received vigorous attentions as the future direction communication system. It is well known that SBS is principally caused by the propagation of back-reflected optical signal. The back-reflected signal is downshifted and normally called as Brillouin Stokes (BS) signal, resulted when the injected Brillouin pump (BP) power exceeds a certain level namely as threshold condition. It is important to realize that the downshifted frequency was usually produced at a constant spacing of 0.08 nm at 1550 nm of BP wavelength from the injected BP signal in the case of a standard single mode fiber (SMF). Once the laser system attained the above threshold condition, the BP power has slightly transferred to the first BS signal. Thus, the BS signal power is depends by the material of gain medium in which allow the propagation of light.

In the past few years, the integration of the narrow linewidth Brillouin laser was implemented in the multi-wavelength Brillouin fiber laser (MWBFL) system and its applications. However, the Brillouin gain is typically very low to achieve high performance of multi-wavelength generation in the Brillouin fiber laser (BFL) operation. Thus, additional of optical amplifier such as an Erbium doped fiber amplifier (EDFA) is necessary to counter the transmission attenuation especially in a long haul optical telecommunication. Alternatively, with its narrow linewidth signal, the MWBFL system offers a lot of advantages for applications such as optical metrology (Subías, Heras, Pelayo, & Villuendas, 2009), fiber-optic sensor (Smith, Zarinetchi & Ezekiel, 1991), high-resolution spectroscopy (Schneider & Schille, 1997), gyroscopes

(Zarinetchi, Smith & Ezekiel, 1981), interferometric sensing (Geng et al., 2006), narrow bandwidth amplification (Ferreira, Rocha & Pinto, 1994), dense wavelength division multiplexing (DWDM) system (Mansor et al., 2011) and other optical fiber communications.

After development of MWBFL system, it also has led to the subsequent studies of multi-wavelength Brillouin-erbium fiber laser (MWBEFL) system (Rahman, Nurdik & A. Rahim, 2014) and multi-wavelength Brillouin Raman fiber laser (MWBRFL) system (Toor, Ahmad Hambali, Abdul-Rashid & Yusof, 2014). These techniques have been widely studied as a prominent method in order to generate a high number BS signal and lower threshold power. However, the major drawback of wavelength tunability and the competition of oscillating modes (self-lasing cavity) at the peak of Erbium doped fiber (EDF) caused the output instability in MWBEFL structure. In this situation, the presence of self-lasing cavity modes constrained the generation of multi-wavelength and output power. Hence, a sufficient amount of BP power is highly needed to suppress the self-lasing cavity modes before entering into the BEFL system. This interference of self-lasing cavity modes are mainly produced by the natural effect of light waves from the EDF. Therefore, this technique is only efficient when the BP wavelength is injected beyond of this free-running EDF laser bandwidth.

Meanwhile, the spectral broadening mechanism of laser modes in the MWBRFL system limits the number of lasing signals. It is important to highlight that the spectral broadening appears within the range of Raman peak gain. The formation of noises in the Raman gain spectrum indicated that the BS signals are not able to suppress the noises from the stimulated Raman scattering (SRS). Another special type of fiber, such as dispersion compensating fiber (DCF) is needed to enhance the Raman gain since the stability of multi-wavelength generation is difficult to obtain. In the MWBRFL system,

the multi-wavelength generation is constrained and only available at the certain Brillouin and Raman pump source (Guy, Chernikov & Taylor, 1998; Zamzuri, Mahdi, Ahmad, Md Ali & Al-Mansoori, 2007).

In order to rectify these limitations, the implementation of MWBFL system utilizing Fiber Bragg Grating (FBG) is highly needed to produce a high number of multi-wavelength generations at a selected wavelength. The combination process of SBS effect and FBG's reflectivity at a center BP wavelength of 1550 nm are blended in this proposed ring cavity laser system. The optimization of different output coupling ratios and fiber lengths are utilized throughout the investigation to minimize the cavity loss in the structure. Even though the utilization of MWBFL system has not been considered seriously before due to low generation of multi-wavelength, this limitation gives the aim and motivation to find another alternative by incorporated with FBG and hence increases the scattering effect in the main gain medium.

1.2 Problem statement

The development and innovation of ring cavity fiber lasers through the years expanded and brought the revolution in the optical communication system and sensing applications. The requirement for an increment in output power for these applications has been developed extensively. This prompted the execution of numerous vital parameters such as cavity loss, number BS signals and optical signal to noise ratio (OSNR) value.

Several investigations of different type optical structure in the laser system have been developed in order to overcome the limitation of generating BS signals and output power (Parvizi et al., 2010; Shirazi et al., 2008; Shirazi, Biglary, Harun, Thambiratnam

& Ahmad, 2008). Recently, linear (bidirectional propagation) and ring cavity (unidirectional propagation) had been extensively studied in the long haul optical communication system (Ajiya, Mahdi, Al-Mansoori, Mokhtar & Hitam, 2009; Rahman, Hitam, Al-Mansoori, Abas & Mahdi, 2011). However, from the previous research on the reversed-S-shaped ring cavity, the laser system constrained a high cavity loss when only 11 BS signal at 1550 nm of BP wavelength was reported in (Rahman, Hitam, Al-Mansoori, Abas & Mahdi, 2011). Therefore, a better solution must be undertaken in this study in order to improve the cavity loss. Of the various structures, the ring cavity received considerable attention because of their appealing low cavity loss, high power efficiency, and low threshold power. This ring cavity can operate in both light propagations namely as clockwise and anti-clockwise direction. The ring cavity is realized by forming a loop constructed together with an optical coupler, Brillouin gain medium and doped fiber. Normally, the cavity loss in the laser system is optimized by different output coupling ratios and determined by percentage of output power. Therefore, to properly address this issue an employment of FBG's reflectivity in the ring cavity offers a direct impact to produce generation of MWBFL as well as reduces the cavity loss in the laser system.

Moreover, a higher number BS signal is another important parameter to achieve an efficient MWBFL system in order to transmit a lot of information at the same time. To attain this condition, the replacement from previous researches work with the hybrid technique MWBFL by utilizing FBG has reduced the cavity loss and subsequently generates a higher number BS signal in the ring cavity. The reflectivity and selective wavelengths of FBG enhances the SBS effect in the Brillouin gain medium and hence takes into consideration to produce large number BS signals. Following that, the cavity loss also has a direct impact on the quality BS signals in term of OSNR value. The